

LAURA ASHLEY

The Laura Ashley Collection

Synonymous with interior decoration, Laura Ashley has joined forces with Kraus® to create a range of Luxury Vinyl flooring. This collection sees the launch of 5 new wood effects that are steeped in the heritage and elegant charm of the Laura Ashley Brand.

The Laura Ashley Collection includes warm natural oaks and greys with a unique natural touch and anti-glare finish, all specially selected to complement the classic Laura Ashley home ranges.



PLANK & PACK SIZE: 1220mm x 180mm x 6mm | 2.2m2 | 10 Planks per Pack

Rigid Core Technology

Combining the classic appeal of natural wood flooring with the added benefits of rigid core luxury vinyl, our collection is the perfect choice for a variety of installations.

Featuring a patented click lock mechanism and a pre-attached acoustic foam underlay, providing added comfort underfoot and sound transmission, it's quicker to install than other flooring types. It is 100% waterproof and is resistant to scuffs and dents, perfect for high traffic areas and is suitable for kitchens and bathrooms.

"No two houses in the world are the same, because everyone likes to put things together in their own way"

Laula Ashley

THE COLLECTION



THE COLLECTION



SOUTHWICK



EMNETH



DALLINGTON



HEPSCOTT



SUTTERTON

SOUTHWICK




PLANK INFORMATION

Name: SOUTHWICK


SKU: LALVTP032

Dimensions: 1220mm x 180mm Coverage (Per Pack): 2.2m²

Planks Per Pack: 10 Thickness: 6mm Wear Layer: 0.5mm A deep and warm walnut shade wood effect with distinctive graining and subtle tonal variation. Deep and rich, this flooring is comforting and restful.



Samples Box Code: EASLALVTP032 10 samples per box



PLANK INFORMATION

Name: **EMNETH** SKU: LALVTP033

Dimensions: 1220mm x 180mm Coverage (Per Pack): 2.2m²

Planks Per Pack: 10 Thickness: 6mm Wear Layer: 0.5mm A versatile and gently grained, weathered light oak wood effect with an underlying Scandi appeal. Calming and understated, this wood effect works effortlessly throughout the home.



Samples Box Code: EASLALVTP033 10 samples per box

DALLINGTON



PLANK INFORMATION

Name: **DALLINGTON**

SKU: LALVTP034

Dimensions: 1220mm x 180mm Coverage (Per Pack): 2.2m²

Planks Per Pack: 10 Thickness: 6mm Wear Layer: 0.5mm A distinctive open grained mix of dark and golden oak wood effect with a rustic and homely feel. This flooring is rich in character and has a confident visual appeal.



Samples Box Code: EASLALVTP034 10 samples per box

HEPSCOTT



PLANK INFORMATION

Name: **HEPSCOTT**

SKU: LALVTP035

Dimensions: 1220mm x 180mm Coverage (Per Pack): 2.2m²

Planks Per Pack: 10 Thickness: 6mm Wear Layer: 0.5mm A classic medium oak wood effect, rich and golden in shade with subtle detailing of knots and grains. This warm and inviting wood effect is a true classic.



Samples Box Code: EASLALVTP035 10 samples per box

SUTTERTON



PLANK INFORMATION

Name: SUTTERTON

SKU: EASLALVTP036

Dimensions: 1220mm x 180mm Coverage (Per Pack): 2.2m²

Planks Per Pack: 10 Thickness: 6mm Wear Layer: 0.5mm A restful and subtle weathered grey wood effect with a contemporary feel. Unassuming yet distinctive, this flooring has a broad appeal.



Samples Box Code: EASLALVTP036 10 samples per box

SPECIFICATIONS

CATEGORY	STANDARD	SYMBOL	PLANK
CE/DOP	EN14041	(€	Pass
UKCA/DOP	EN14041/2004	UK CA	Pass
Usage Classification	EN485		31-34
Manufacturing Standard	EN649		EN649
Total Thickness	EN428		6mm
Wear Layer Thickness	EN429	(X)	0.5mm
Weight	EN430	ß	2100kgs/m³
Abrasion Resistance	EN660-1/2		Group T
Residual Indentation	EN433	و المالية الما	Pass
Dimensional Stability	EN434	K Z	Pass
Slip Resistance	DIN 51130:2014-02	C C C C C C C C C C C C C C C C C C C	R10
Chemical Resistance	EN423	*	Pass
Colour Fastness to Light	EN20105-B02	3	≥ 6 class
Flammability	EN 13501-1 Class Bfl-S1	B _m -s1	Pass
Castor Chair Resistance	EN425		22130
Impact Sound Insulation	ENISO140-8		IIC=72 Test Method: ASTM E492-09(2016)/ASTM E989-21 STC=73 Test Method: ASTM E90-09(2016)/ASTM E413-16
Thermal Resistance	EN12667		0.033(m2.k)/W
Electrostatic Performance	EN1815		0.2 Kv
Emissions	Floor Score		Pass
Phthalate Free	EN 14372:2004		Pass



