

LAURA ASHLEY

SINCE 1953

Luxury Vinyl Flooring Technical Specs

CATEGORY	STANDARD	SYMBOL	RESULT
CE/DOP	EN14041		Pass Certificate No: CPR-24/0625-1
UKCA/DOP	EN14041/2004		Pass Certificate No: FLO0330731 2218 1, 22798/4
Usage Classification	EN485		23, 34, 43
Manufacturing Standard	ISO 10874:2009		ISO 10874:2009
Total Thickness	ISO 24346:2006		6mm
Wear Layer Thickness	ISO 24340:2006		0.5mm
Weight	ISO 23997:2007		21 kg/m²
Abrasion Resistance	EN660-1/2		Group T Type 2
Residual Indentation	ASTM F1914-18(2023)		Pass <0.1 mm - Avg: 4.1% Max: 5.2% - Min: 3.3%
Dimensional Stability	ASTM F2199-20		Pass X Direction: -0.06% Y Direction: -0.06%
Slip Resistance	SS485:2022 & AS4586-2013		R10 Critical angle of inclination: 11.8°
Chemical Resistance	ASTM F925:2002		Excellent
Colour Fastness to Light	ISO105-B02:2014		Grade (B.W.S) ≥ 6 class
Flammability	EN 13501-1 Class Bfl-s1		Pass Bfl-s1
Castor Chair Resistance	ISO/TR 4918:2009		25000
Impact Sound Insulation	ASTM E989-2006		IIC=61 STC=74
Thermal Resistance	EN12664:2001		0.040 (m2.k)/W
Electrostatic Performance	EN1815		0.6 Kv
Emissions	Floor Score		Pass A+
Phthalate Free	EN 14372:2004		Yes
Warranty			25 years residential 10 years commercial

Manufactured under licence by QEP Co. UK Ltd.

® & © 2024 Laura Ashley Brands.

QEP Co. UK Ltd., The Maltsters, Wetmore Road, Burton upon Trent, DE14 1LS