

	Standard	Result
 Size		See separate table
 Thickness	ISO 24346	6.5 mm
 Wear layer	ISO 24340	0.55 mm
Locking mechanism¹		2G™ angling installation system
Surface treatment		PU coating
Warranty²	Commercial Residential	15 years 20 years
 Bevelled edge		Micro
 Mass per unit area	ISO 23997	7480 g/m ²
 Standards	EN 16511	Pass (Multilayer modular floorcovering panels)
 Classification	ISO 10874 - Commercial ISO 10874 - Domestic	33: Commercial heavy 23: Domestic heavy
 Reaction to fire	EN 13501-1	B _{f1} -s1
 Staining resistance	EN 438-2	Pass (Grade 5)
 Light fastness	EN ISO 105-B02	Pass (≥ 6)
 Abrasion resistance	EN 13329 Annex E	Pass (> 4000 cycles)
 Furniture chair leg	EN 424	Pass (No visible damage)
 Dimensional stability	BS EN ISO 23999	Pass (< 0.25%)
 Swelling	ISO 24336	Pass (0.2%)
 Acoustic impact noise reduction	EN ISO 10140-1:2016 and EN ISO 10140-3:2010+A1:2015	ΔL _w = 19 dB ΔL _{LIN} = 11 dB
 Indentation - residual	ISO 24343-1	Pass (≤ 0.1 mm)
 Impact resistance	EN 13329 Annex F	Pass (> 1800 mm)
 Castor chair continuous use	EN 425/ISO 4918	Pass (25,000 cycles)
 Thermal resistance	ISO 8302	0.052 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance³	EN 13893 EN 16165 Annex B/DIN 51130	DS R10
 Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
 Adhesive		None required, Please install according to our installation instructions.
 Environmental	Indoor Air Comfort Floorscore SCS-EC10.3-2014 v4.0 ISO 14001 / ISO 9001	Gold certification; Compliant low emitting VOC emissions. Indoor air quality certified; Compliant low emitting VOC emissions. Manufactured to quality and environment management systems standard
 Recycling		Suitable
 Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

UK: 01386 820110 | ROI: 01 6569887

Email: info@palioflooring.com

Visit: www.palioflooring.com

Feb 23



20



EN 14041: 2004 (DOP 2017/PCore/EN/02)
Notified body 0493
Floor coverings (internal)
ISO 10874 Class 23/33
Manufactured to EN 16511



21

BS EN 14041: 2004 (DOP 2021/UKCA/PCore/01)
Approved body 0321
Floor coverings (internal)
ISO 10874 Class 23/33
Manufactured to EN 16511



	Product Code	Size		Box Quantity		Slip Resistance EN 16165 Annex B / DIN 51130	LRV
		mm	inches	m ²	Pieces		
Wood Designs	RCP6503	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	28
	RCP6504	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	26
	RCP6507	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	17
	RCP6508	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	41
	RCP6509	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	12
	RCP6532	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	30
	RCP6533	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	27
	RCP6544	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	31
	RCP6546	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	40
	RCP6547	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	32
	RCP6548	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	13
	RCP6549	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	40
	RCP6550	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	45
	RCP6551	1220.0 x 179.0	48.03" x 7.05"	2.184	10 Planks	R10	29
	SM-RCP6550	596.0 x 149.0	23.46" x 5.87"	1.954	22 Planks	R10	45
	SM-RCP6551	596.0 x 149.0	23.46" x 5.87"	1.954	22 Planks	R10	29
	SM-RCP6533	596.0 x 149.0	23.46" x 5.87"	1.954	22 Planks	R10	27
Stone Designs	RCT6303	307.0 x 600.0	12.09" x 23.62"	1.842	10 Tiles	R10	40
	RCT6304	307.0 x 600.0	12.09" x 23.62"	1.842	10 Tiles	R10	11
	RCT6306	307.0 x 600.0	12.09" x 23.62"	1.842	10 Tiles	R10	60
	RCT6307	307.0 x 600.0	12.09" x 23.62"	1.842	10 Tiles	R10	40
	RCT6308	307.0 x 600.0	12.09" x 23.62"	1.842	10 Tiles	R10	30